



TB264H1

LOAD DATA

Bullet Diameter: 264"
Bullet Weight: 140gr
Bullet Type: Speer® Impact

More reloading data can be found at speer-ammo.com

6.5 Creedmoor 24" SAAMI chamber Universal Receiver test barrel COAL Tested 2.825" | Federal 210 Primer | Federal Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	43.2	2662	45.9	2828
Alliant Power Pro® 4000	41.4	2632	44.8	2816
Alliant Reloder® 16	39.1	2632	42.1	2799
Alliant Reloder® 17	38.2	2615	40.5	2773
Hodgdon H414	38.9	2604	41.3	2757
Alliant Power Pro® 2000	37.3	2597	39.9	2753
Hodgdon H4350	38.3	2552	41.2	2719
IMR 4451	37.4	2515	40.6	2693

6.5 PRC 24" SAAMI chamber Universal Receiver test barrel COAL Tested 2.955" | Federal 210 Primer | Hornady Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Hodgdon Retumbo	55.1	2738	61.1	3025*
Accurate Magpro	54.4	2711	60.4	3009
Alliant Reloder® 26	52.1	2721	57.7	3007
Alliant Reloder® 25	54.1	2777	59.2	3001
Hodgdon H1000	52.9	2771	58.3	2982
IMR 7828	49.9	2704	55.3	2955
Alliant Reloder® 22	48.2	2750	53.3	2937

6.5-284 Norma 24" SAAMI chamber Universal Receiver test barrel COAL Tested 2.980" | Federal 210 Primer | Lapua Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	49.8	2612	55.1	2933
Hodgdon H1000	51.4	2681	57.1	2921*
Alliant Reloder® 23	46.8	2632	51.9	2887

6.5-300 Weatherby Magnum

24" SAAMI chamber Universal Receiver test barrel
COAL Tested 3.600" | Federal 215 Primer | Weatherby Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 33	75.6	2881	83.9	3172
Hodgdon Retumbo	69.9	2859	77.5	3141
Alliant Reloder® 26	66.4	2840	73.9	3115

6.5x55 Swedish (SAAMI Pressure)

24" SAAMI chamber Universal Receiver test barrel
COAL Tested 3.150" | Federal 210 Primer | Federal Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	41.0	2358	45.2	2624
Alliant Reloder® 22	39.2	2388	43.2	2600
Alliant Reloder® 19	38.3	2367	42.5	2595
Alliant Reloder® 23	37.2	2375	41.1	2574
Alliant Reloder® 17	35.0	2401	38.2	2570

6.5x55 Swedish (Strong Commercial Actions)

24" SAAMI chamber Universal Receiver test barrel
COAL Tested 3.150" | Federal 210 Primer | Federal Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	41.0	2358	48.2	2813
Alliant Reloder® 22	39.2	2388	47.1	2808*
Alliant Reloder® 19	38.3	2367	46.2	2796*
Alliant Reloder® 17	35.0	2401	41.8	2760
Alliant Reloder® 23	37.2	2375	44.6	2752

264 Winchester Magnum

24" SAAMI chamber Universal Receiver test barrel
COAL Tested 3.340" | Federal 215 Primer | Hornady Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 33	67.3	2728	74.3	3060*
Hodgdon Retumbo	61.0	2709	67.6	3021
Alliant Reloder® 26	59.0	2756	64.5	3019

26 Nosler 24" SAAMI chamber Universal Receiver test barrel COAL Tested 3.340" | Federal 215 Primer | Nosler Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 33	75.4	2928	83.9	3216
Hodgdon Retumbo	69.5	2957	76.4	3159
Alliant Reloder® 26	62.5	2861	69.5	3094

260 Remington

24" SAAMI chamber Universal Receiver test barrel
COAL Tested 2.900" | Federal 210 Primer | Federal Brass

POWDER	STARTING CHARGE		MAX CHARGE	
	CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Power Pro® 4000	42.0	2590	45.6	2802*
Alliant Reloder® 16	39.6	2599	42.4	2787
Alliant Reloder® 17	39.8	2600	43.1	2787
IMR 4831	42.0	2574	45.4	2771*
Accurate 4350	40.6	2582	43.6	2771*
Hodgdon H414	39.6	2574	42.4	2766
IMR4350	40.0	2561	43.4	2751*
Hodgdon H4350	38.5	2553	42.1	2746
Winchester W760	38.4	2553	42.2	2734
IMR 4064	33.8	2468	37.1	2662

* indicates compressed load with our tested cartridge brass
Barrel twist of 1:8 or faster recommended